



Espacenet

Bibliographic data: EP 0585626 (A1)

Laminated mineral fibre mat.

Publication date: 1994-03-09

Inventor(s): HAEBICH STEFANIE [DE]; KRONEIS ALFRED [DE]; HEIDEL PETER DR [DE] +

Applicant(s): HOECHST AG [DE] +

Classification:

- **international:** **B32B17/04; B32B27/18; B32B27/38; B32B27/42; B32B5/26; B32B7/12; D04H13/00;** (IPC1-7): D04H13/00
- **European:** B32B5/26; D04H13/00B4

Application number: EP19930112342 19930802

Priority number(s): DE19924227035 19920814


Also published as:

- NO 932884 (A)
- JP 6155650 (A)
- FI 933572 (A)

Cited documents: EP0453968 (A2) DE3734239 (A1) US3361610 (A) GB946040 (A) [View all](#)

Abstract of EP 0585626 (A1)

There is described a flame-retardant, easy-to-process mineral fibre mat laminated on one or both sides with a preconsolidated synthetic fibre nonwoven having a basis weight from 10 to 100 g/m² and made of staple or continuous polyester fibre. The mineral fibre mat is held bonded to the synthetic fibre nonwoven by an adhesive composition containing 20-60% by weight (calculated solid on solid) of an organic, nitrogen- and phosphorus-containing flameproofing agent, the adhesive composition being present in an amount from 3 to 30 g/m² per side of the mineral fibre mat. There is also described an advantageous process for producing this laminated mineral fibre mat.



Last updated: 26.04.2011 Worldwide Database 5.7.22; 92p